







	USER GUIDE					
Document Code No	Document Code No Release Date Revision Date Revision No					
CE-11 - 009 28.10.2016 03.11.2020 02						

1. GENERAL INFORMATION 1.1. PURPOSE AND SCOPE:

AOSM 40 ELECTRICALLY ANGLED AUTOMATIC SIZING MACHINE's safe installation, explanation of the working system, defining the maintenance and usage processes, ensuring safely use services of the product, enabling users in the light of the user guide to use the machine as the most suitable, protected from dangers that may occur during use, ensuring the most efficient operation, reducing downtime for cleaning and maintenance work to increase productivity.

The product, whose name and type is given below, that you have purchased within this scope in accordance with the regulations and standards specified in ISO 9001:2015 Quality Management System, subject to factory production control, accredited certified by TSEK and TSE HYB, meeting the requirements of 2006/42/AT machinery safety regulation and referenced 2006/95/AT the Low Voltage Regulation is produced in our production factory in accordance with quality criteria.

The relevant equipment and materials used in AOSM 40 Electrically Angled Automatic Sizing Machine are subject to relevant regulations and in accordance with our Supplier Evaluation Criteria and are supplied from companies or organizations approved by us.

1.2. ABOUT THE GUIDE:

Please, read this user manual before using AOSM 40 Electrically Angled Automatic Sizing Machine and follow all these rules while using it. Perform all your applications during use as instructed in the user manual. Store it in a safe place for future use. In case you give this AOSM 40 Electrically Angled Automatic Sizing Machine to 2nd or 3rd parties, you must also give this user guide.

The items listed below are prepared and presented for safety and compliance of purchased AOSM 40 Electrically Angled Automatic Sizing Machine, which is in safe, all regulatory obligations fulfilled and in good quality, and as well as for your own safety.

1.3. INFORMATION ABOUT PRODUCTION COMPANY:

Tıtle		KAPTANLAR MACHINERY AND HYDRAULIC INDUSTRY TRADE LIMITED COMPANY		
Adress		ORGANIZED INDUSTRIAL ZON	IE 4. STREET NO: 3 AFYONKARAHİSAR / TURKEY	
Telephone		+90 (272) 221 12 00 - 01		
Fax		+90 (272) 221 12 02		
e-mail		info@kaptanlar.com.tr		
Web Adress		www.kaptanlar.com.tr		
Chamber Of Co	mmerce	Registiration Number	Afyonkarahisar 8977 / 7956	
Tax Office Regi	stiration	Number	KOCATEPE V.D. 499 011 8384	
Registirated Tra	ide Marl	rk KAPTANLAR (TPE; 08.10.1992/136020)		
TSE HYB Docu	ment No)	03-HYB-1657	
ISO 9001:2015	Quality 1	Mang. System Document No	K-QM-4717	
TSE TSEK Doc	ument N	lo .	020248-TSEK-01/01	
Company Discription				









	USER GUIDE					
Document Code No	Document Code No Release Date Revision Date Revision No					
CE-11 - 009 28.10.2016 03.11.2020 02						

2. MACHINE TECHNICAL INFORMATION;

2.1. PRODUCT SPESIFICATION:

ENGINE TYPE	ELECTRICAL	
ENGINE POWER	40 hp, 30 kW	
ENGINE SPEED	1500 rev/min (rpm)	
ENGINE VOLTAGE	380 V	
WALKING ENGINE	Automatic Speed Control with Reductor	
THE WIRE USED	Diamond	
CUTTING SPEED	8 - 15 m ² surface area/hour	
CAPACITY	35 - 50 m	
WORKING ANGLE	180° in any position	
WATER NEED	200 liter/hour	
PULLEY DIAMETER	60 cm, 1 unit	
WEIGHT	800 kg	
LENGTH	4500 mm	
HEIGHT	1700 mm	
WIDTH	1600 mm	

2.2. PRODUCT WARRANTY INFORMATION:

REGISTIRATED TRADEMARK	KAPTANLA	R (TPE; 08.10.1992/136020)	
GENERAL COMMERCIAL DISCRIPTION	AOSM 40 ELECTRICALLY ANGLED AUTOMATIC SIZING MACHINE; The cutting process enables the diamond wire with the help of a pulley to be rotated around the marble block for cutting and separating it. When the machine starts, the motor rotates the shaft and turns the pulley and hence the marble block is cut with the help of diamond wire. The engine is fixed on a car and a pulley connected to the engine shaft is used. The slack in the wire during cutting is automatically removed by the travel motor. Thus, the cutting process is completed. During the cutting process of the electric diamond wire block cutting machine, water is sent to the cutting area with hoses and it can be used with the help of a valve. Thanks to the water, the cutting tool (diamond wire) is prevented from overheating and the marble dust is removed from the cutting area.		
BUSINESS MODEL	AOSM 40		
LIFETIME	10 YEARS		
WARRANTY PERIOD	2 YEARS		
SERVICE PERIOD	30 working	<u>days</u>	
TPE - INDUSTRIAL DESIGN REGISTRATION DATE, NO		03.02.2012-2012/00748	
TPE - PATENT. UTILITY MOD REGISTRATION DATE, NO	EL	22.10.2012 – TR2012 / 02293	
Œ EC DECLARATION OF COMPUBLICATION DATE REGION,		28.10.2016, RVZ.02/ 40.09.2020 EC/KM-2012/CE-05.09	
Œ PRODUCT LABEL PUBLICATION DATE, NO		28.10.2016, RVZ.02/ 40.09.2020, CE/09-06	
Œ PRODUCT SPECIFICATION PUBLICATION DATE, NO	N	28.10.2016, RVZ.02/ 40.09.2020, CE-04-03	
Œ FACTORY PRODUCTION CONTROL CERTIFICATE DATE, NO		28.10.2016, EC-KM-2015-0002/CPD	










	USER GUIDE					
Document Code No	Document Code No Release Date Revision Date Revision No					
CE-11 - 009	28.10.2016	03.11.2020	02			

2.3.MACHINE DIMENSIONS:




A) LENGTH: 4500 mm

B) HEIGHT: 1700mm

C) WIDTH: 1600mm



2.4. MAIN PARTS OF MACHINE:



CAR, ENGINE, CAB, CHASSIS, ELECTRICAL PANEL INSTALLATION DATASHIPS

11	PANO	A40-01-11	1
10	KABLO TAŞIYICI	A40-01-10	1
9	TAKIM SANDIĞI	A40-01-09	1
8	MOTOR KABINI	A40-01-08	1
7	30 KW 40 HP 1500D/D GAMAK	A40-01-07	1
6	ARABA MONTAJI	A40-01-06	1
5	MUHAFAZA BORUSU	A40-01-05	1
4	MUHAFAZA	A40-01-04	1
3	3 KASNAK PULU		1
2	2 60 LIK KASNAK		1
1	ŞASE MONTAJI	A40-01-01	1
PARÇA NO	PARÇA İSMİ	TANIM	ADET

CIZEN 20.08.2020 NURULLAH ÖZÇELİK KONTROL ONAY ÖLÇEK 1:20 CAR CHASSIS ASSEMBLY

KAPTANLAR®
MAKINA VE HIDROLIK
MACHIBETY AND HYDRAULICS
RESIM NUMARASI

A40-01










USER GUIDE					
Document Code No Release Date Revision Date Revision No					
CE-11 - 009 28.10.2016 03.11.2020 02					

2.5. MACHINE TECHNICAL DRAWINGS:

2.5.1. AOSM 40 CAR, CHASSIS BODY ASSEMBLY



CHASSIS, WALKING KIT,
${\color{blue} \textbf{HUB}}, {\color{blue} \textbf{WHEEL}}, {\color{blue} \textbf{ASSEMBLY}}$

	TARİH	İSİM	İMZA
ÇİZEN	20.08.2020	NURULLAH ÖZÇELİK	
KONTROL			
ONAY			
ÖLÇEK			
1:20	AOSM4	10 CHASSIS ASSEI	ИBLY



	TARİH İSİM	İMZA	The same of the sa	
PARÇA NO	PARÇA	ISMİ	TANIM	ADET
1	50X15X100		A40-01-01-01	2
2	1 1/2" BOR	1 1/2" BORU 15 CM		2
3	80X10X240 LAMA		A40-01-01-03	4
4	1 1/2" BORU	1 1/2" BORU 4 METRE		2
5	50 NPU 5	50 NPÚ 5 METRE		2
6	TOFAŞ PC	TOFAŞ PORYASI		2
7	13" JA	13" JANT		2
8	13" LA	13" LASTÍK		2
9	100 NPU		A40-01-01-09	1
10	OASM40 MA	OASM40 MAKİNA -11		1
11	40X15X70	LAMA	A40-01-01-11	1
12	AOSM 40 M	AKİNA-7	A40-01-01-12	2
13	KRAMİYER DİŞI	I 3,2 METRE	A40-01-01-13	1
14	100X40X430		A40-01-01-14	5
15	80X160 PROF		A40-01-01-15	2
16	SWİTCH L	77.	A40-01-01-16	2
17	Q30 TRANS	MISYON	A40-01-01-17	2
18	AOSM 40 M	AOSM 40 MAKİNA -6		2
19	60X60X3 PROFİL 35 CM		A40-01-01-19	2
20	60X10X140	A40-01-01-20	2	
21	AOSM 40 M.	akina -8	A40-01-01-21	2

	TARİH	İSİM	IMZA	0
ÇİZEN	20.08.2020	NURULLAH ÖZÇELİK		KAPTANLAR®
KONTROL				MAKINA VE HIDROLIK MACHINERY AND HYDRAULICS
ONAY	BOD	Y ASSEMBLY		WACHINERY AND HYDRAULES
ÖLÇEK	400	SM40 CHAS	919	RESİM NUMARASI
1:20		SSEMBLY-2		A40-01-01



AOSM 40 Electrically Angled Automatic Sizing Machine Technical, drawings of the visual image










Document Code No	Release Date	Revision Date	Revision No
CE-11 - 009	28.10.2016	03.11.2020	02

This document is KAPTANLAR MACHINERY AND HYDRAULICS INDUSTRY TRADE LTD. COMPANY's. All rights are reserved.

No part of this publication my be used or changed without the permission of the publisher. Con not be stored in a system to be used again and con not be reproduced by electronically or mechanical photocopying. Bound copies are invalid. This kind of people and organizations in the legal process is initiated initiatives.

2.5.2. AOSM40 CAR, CHASSIS ASSEMBLY



1:50		ALLATION DAT		A40-01-06
ÖLÇEK	CHARG	SIS BODY ASSE	MDIV	RESİM NUMARASI
ONAY				MACHINERY AND HYDRAULOS
KONTROL	20.00.2020	HOROLD III OLYLLIK		MAKINA VE HIDROLIK
ÇİZEN	20.08.2020	NURULLAH ÖZÇELİK	INILA	™ KAPTANLAR®
ARÇA N	TARİH	PARÇA İ	iMZA	TANIM ADE
ADOA	10	AOSM 40 MA		7.107.707.707
2		MUHAFAZA E		A40-01-06-02 2 A40-01-06-01 3
3		40X10X710		A40-01-06-03 2
4		AOSM40 MA		A40-01-06-04 1
5		AOSM40 MA	A STATE OF THE STA	A40-01-06-05 1
6		3/8 GRASÖRLÜK		
7		40X10X430		A40-01-06-07 1
8		51118 RULMAN		A40-01-06-08 1
9		SONSUZ [A40-01-06-09 1
10		6205 RULMAN		A40-01-06-10 2
11		6205 RUL		A40-01-06-11 2
12		51118 RULMAN		A40-01-06-12 2
13		SONSUZ VÍDA		A40-01-06-13 1
14		50X10X340 LAMA		A40-01-06-14 1
15		TEKER		A40-01-06-15 4
16		M10X20 AKB		A40-01-06-16 4
17		ÖZEL PI	JL	A40-01-06-17 4
18		6305 RULA		A40-01-06-18 8
19		M16X70 AKB VE		A40-01-06-19 4
20		TEFLON TAN	MPON	A40-01-06-20 4
21		AOSM 40 MA	KINA -6	A40-01-06-21 4
22		TEKER N	NILI	A40-01-06-22 2
23		AOSM40 MA	KINA -1	A40-01-06-23 1
24		100X40X610	PROFIL	A40-01-06-24 2
25		AOSM 40 MA	KINA-5	A40-01-06-25 1
26		GÖBE	<	A40-01-06-26 1
27		MOTOR LA	MASI	A40-01-06-27 2
28		50X10X50 L		A40-01-06-28 4
29		AOSM 40 MA	KINA-4	A40-01-06-29 4
30		M12X20	AKB	A40-01-06-30 6
31		KARE SOMUN		A40-01-06-31 1
32		SABİTLEME KARESİ AOSM 40 MAKİNA-12		A40-01-06-32 3

2.6. ELECTRICAL CIRCUIT DIAGRAMS;

2.6.1. CIRCUIT DIAGRAM:

AOSM 40 ELECTRICAL PANEL, MATERIAL LIST



,	
PART NO	PART NAME
1	5X63 MACHINE PLUG
2	TURBO 3 PHASE AMPERMETER
3	3X63 RIGHT-LEFT INVERTER
4	45-63 ENGINE PROTECTION SWITCH
5	MC65 CONTACTOR
6	TIMER
7	PHASE PROTECTION RELAY
8	1X16 FUSE
9	100/5 CURRENT TRANSFORMER
10	MC18 CONTACTOR
11	1.6-2.5 ENGINE PROTECTION SWITCH
12	1X10 CONTROL CABLE
13	6 BUTTON CONTROLLER










USER GUIDE					
Document Code No	Release Date	Revision Date	Revision No		
CE-11 - 009 28.10.2016 03.11.2020 02					

2.6.2. ELECTRICAL CONNECTION METHOD:



MATTERS TO BE CONSIDERED BEFORE USE;

3.1. GENERAL INFORMATION BEFORE USE:

- 3.1.1. During the warranty coverage period, no part of AOSM 40 Electrically Angled Automatic Sizing Machine, which is delivered as Robust and Quality Controlled and Approved to the Customer can be changed without the knowledge of the manufacturer, except by the relevant authorized persons. No additions or changes can be made to or removed from all its equipment. The machine that has fallen into such situations is out of warranty and the manufacturer does not accept responsibility. AOSM 40 Electrically Angled Automatic Sizing Machine's format and visual changes should not be made on it. Such changes cause it to be out of warranty in accordance with legal regulations. The manufacturer is not responsible for machines exposed to such situations. The machine exposed to such situations is out of warranty.
- 3.1.2. The manufacturer is not responsible for malfunctions, problems and accidents caused by improper use of AOSM 40 Electrically Angled Automatic Sizing Machine and non-compliance with the instructions. Machines that occur in these situations are out of warranty and technical service repair and necessary spare part replacements belong to the customers
- 3.1.3. Complying with all the rules and safety precautions mentioned in the user manual, all the issues explained, the issues mentioned in the maintenance user manuals are in compliance with all legal regulations in terms of human health, life and property safety.
- 3.1.4. The substances included in the User Guide are presented for your information for safety of AOSM 40 Electrically Angled Automatic Sizing Machine bought, your safety and your users's safety in terms of crafted to conform, all legal obligations fulfilled, subject to Quality and CE Marked Product Safety ISO 9001:2015 Quality management system Accredited System Certified, TSE/TSEK.
- 3.1.5. While using AOSM 40 Electrically Angled Automatic Sizing Machine, you encounter problems or situations that you are not sure about, you should inform the authorized service of our organization without intervening.
- 3.1.6. This User's Guide does not contain repair information. In case of any problem, you should only contact our authorized service.











E 1							_
	<i>V</i> —	_	p. 100/		-	D	
		_		_	-	# # 1	
	P 1	_		.	- II	B 📂 A	
		-					

332.1. 33.122						
Document Code No	Release Date	Revision Date	Revision No			
CE-11 - 009	28.10.2016	03.11.2020	02			

3.2. CUSTOMER SERVICES:

Once customer sales realized, dispatch and delivery operations of AOSM 40 Electrically Angled Automatic Sizing Machine are carried out after quality final and it is delivered to the customer or its authorized representative, and the shipment is carried out by private transport companies. About the use of the machine and the points to be considered, warranty conditions, maintenance, repair, cleaning, etc. general and technical information on the subject and information on connection types, Pre-delivery trainings are given to the relevant technical and user personnel of the user company on all issues that should be considered during use and in case of emergency.

3.3. SERVICE ACTIVITIES:

Servicing of all of our machines produced will be performed by our technical team, with the full address and contact information below, in accordance with the rules of this user guide during the warranty period and after the end of the warranty, according to the rules of the Certificate of Competence and TSE Certificate of After Sales Services.

3.4. SCOPE OF WARRANTY:

Kaptanlar Machinery and Hydraulic Industry Trade Limited Company gives a two-year warranty for all the machines produced. Parts that fail or deteriorate within the warranty period are examined and recorded by authorized service technical personnel. If the resulting malfunction or deterioration is due to manufacturing faults, the necessary parts are replaced and/or repaired and made usable. User errors are evaluated as out of warranty and service provided. All materials and spare parts that will change out of warranty are delivered to the customer as soon as possible with the service process.

3.5. DOMESTIC DEALERS:

Central: KAPTANLAR MACHINERY AND HYDRAULIC INDUSTRY TRADE LIMITED COMPANY

Address: ORGANIZED INDUSTRIAL ZONE 4. STREET NO: 3 AFYONKARAHİSAR / TURKEY

Phonel: +90(272) 221 12 00 - 01 **Fax:** +90(272) 221 12 02

e-mail: info@kaptanlar.com.tr Web Address: www.kaptanlar.com.tr

Department:

Address:

Phonel: Fax:

e-mail: Web Address:

3.6. MANUFACTURER AND AUTHORIZED SERVICE INFORMATION:

<u>AUTHORIZED SERVICE STATION SERVICE LOCATION AND SPARE PARTS SUPPLY ADDRESSES</u>



Central: KAPTANLAR MACHINERY AND HYDRAULIC INDUSTRY TRADE LIMITED COMPANY

Address: ORGANIZED INDUSTRIAL ZONE 4. STREET NO: 3 AFYONKARAHİSAR / TURKEY

Phonel: +90(272) 221 12 00 - 01

Fax: +90(272)2211202 e-mail: info@kaptanlar.com.tr Web Address: www.kaptanlar.com.tr Working Hours: Weekdays 09.00 – 18.00

+90 272 221 12 01 & 0 533 309 45 92









USER GUIDE					
Document Code No	Release Date	Revision Date	Revision No		
CE-11 - 009 28.10.2016 03.11.2020 02					

4. USE;

4.1. BASIC OPERATION FEATURES:

- **4.1.1.** AOSM 40 Electrically Angled Automatic Sizing Machine is manufacture according to the safety rules of the relevant standards and regulations.
- 4.1.2. The user guide must be read before using the machine.
- 4.1.3. AOSM 40 Electrically Angled Automatic Sizing Machine should be used only for the purpose of production.
- 4.1.4. The machine must be used by the person in charge, and the responsible person must receive training about the machine, must know the machine, must have a good command of the working principles, must be aware of how to respond in an emergency, and must be aware of the risks that may occur during the operation of the machine. Machines should never be used by personnel who do not have this knowledge and competence.
- **4.1.5.** In case of any functional irregularity, machine equipment and design changes, deterioration, especially changes that do not comply with the machine working principles and safe working efficiency, the machine should not be operated and these problems should be eliminated by taking immediate action.
- **4.1.6.** Before starting to use AOSM 40 Electrically Angled Automatic Sizing Machine, the machine manager should check before each use that the waterway connected to the machine is open, the existing electrical connections are in working condition, the cutting diamond wire connection is intact and in working condition.
- 4.1.6. Our Company (Manufacturer Company of the AOSM 40 Electrically Angled Automatic Sizing Machine in use) will not be liable in case of failure in obeying the rules explained above.

4.2. TRANSPORTATION OF THE MACHINE AND PLACEMENT IN THE WORK AREA:

- 4.2.1. The vehicles to carry the machine must be in a position suitable for the dimensions of the machine (see Page 2, Item 2.1), that can take the weight, length and volume of the machine.
- 4.2.2. During the loading and unloading of the machine to the transport vehicle, the transport hook on the main body must be used. (See page 3, item 2.3 figure no. 3.) The machine can be easily transported by means of the chain rope that is passed through this carrying hook with a lifting capacity of minimum 800 Kg from the point shown. During the lifting, loading, carrying and lowering of the machine, careful action should be taken not to damage any part or part of it.
- 4.2.3. The machine must be immobilized during the transportation by placing resistant wedges to the bottom.
- **4.2.4.** Necessary measures should be taken to prevent the transport vehicles and containers from taking in water, moisture or precipitation. The vehicles must be firm and mustn't change shape under load.
- **4.2.5.** Regulation of the legal documents and insurance certificates prior to shipping is customer's responsibility.
- **4.2.6.** Measures are taken by our staff during the installation process and pre-shipment controls are made by us. Our company isn't responsible for the negativities that may occur during shipping.
- **4.2.7.** The customer must control if there is a problem occurred during the shipping before receiving the delivery. If there is a problem, the customer should contact with the insurance company. Our company will not be responsible.
- 4.2.8. The area where the machine will be placed must be firm and mustn't change shape under load. The area should be in the appropriate size. After placing, the machine should be in square. At the each side of the machine, a minimum 3 m space and at the back side, 2 m space should be left. A 10 cm. circled protection tape must be created.
- 4.2.9. The conditions explained above should be checked certainly by the customer's competent staff.









USER GUIDE					
Document Code No	Release Date	Revision Date	Revision No		
CE-11 - 009 28.10.2016 03.11.2020 02					
This decomment is MADTANUA	D MACHINEDY AND HYDDAHLIOC	INDUCTOR TO A DE LETO COMO ANVI-	All aladete and accounted		

4.2.10. Our company will not be liable in case of failure in obeying rules explained above and the problematic machines will be out of guarantee.

4.3. DAILY OPERATIONS OF THE MACHINE:

- 4.3.1. AOSM 40 Electric Angle Automatic Counting Machine; the daily running operation must be initiated by the trained personnel with sufficient knowledge. Competent staff must certainly read the users guide and obey the rules.
- 4.3.2. Before starting daily operations, the machine working area and its environment should be clean.
- **4.3.3.** The electrical connection of the machine must be made by qualified personnel in accordance with its purpose. The electrical connection of the machine must be made in such a way that it reaches the control panel and the electrical panel (see Page 6 Item 2.6.2). The supply of the machine panel is attached. The operating direction is given by the switch.
- 4.3.4. In the activity area, the machine is placed in such a way that it can cut in accordance with the area to be cut. All settings are checked again before running.
- 4.3.5. The diamond wire that will perform the cutting process is checked. Adjustment is made from the ampermeter according to the existing wire and the area to be cut, ensuring that it is in the position attached to the pulley.
- **4.3.6.** The working process is started by pressing the walking start button and by determining the walking direction after the pulley takes the required speed with the start of the machine working process.
- **4.3.7.** The machine starts working in the selected current direction. When the activity is finished, the machine is stopped and then the necessary maintenance control is done by the authorized person. It is started to operate again during the day with the operating system described above.
- **4.3.8.** AOSM 40 Electric Angle Automatic Counting Machine's Control Panel Elements are listed in the material on Page 6 Circuit Diagram in Item 2.6; its electrical panel is shown.
- 4.3.9. Our company cannot be held responsible if the above-described items are not provided. Machines exposed to this position are out of warranty.

4.4. MACHINE MAINTENANCE INFORMATION AND SETTINGS;

4.4.1. GENERAL MAINTENANCE RULES;

- **4.4.1.1.** The users of the machine, cleaning and maintenance responsibles should be defined and maintenance times should be planned by each user company, the cleaning and maintenance of the entire machine after each use must be checked for conformity by the authorities in accordance with the plans.
- **4.4.1.2.** Before cleaning, maintenance and troubleshooting, all operating buttons must be brought to the stop position, the emergency stop button must be pressed, the main machine switch should be turned off and the machine should not be started before the maintenance is completed.
- **4.4.1.3.** A visible size (MAINTENANCE) sign should be hung by by the responsible person performing cleaning, maintenance, troubleshooting, or repair in order toprevent any other intervention or operation of the machine.
- **4.4.1.4.** Electricity of the machine should be disconnected from the main line before cleaning, maintenance and troubleshooting. Wait for 5-6 minutes before maintenance and troubleshooting allowing for stopping of the moving partsand for discharging the static electricity in the machine. The machine's electrical grounding connections must not be interrupted after disconnecting and must be checked.













Document Code No	Release Date	Revision Date	Revision No
CE-11 - 009	28.10.2016	03.11.2020	02

This document is KAPTANLAR MACHINERY AND HYDRAULICS INDUSTRY TRADE LTD. COMPANY's. All rights are reserved.

No part of this publication my be used or changed without the permission of the publisher. Con not be stored in a system to be used again and con not be reproduced by electronically or mechanical photocopying. Bound copies are invalid. This kind of people and organizations in the legal process is initiated initiatives.

- **4.4.1.5.** Personnel to perform cleaning, maintenance and troubleshooting must be authorized by the user company and must have received on-the-job training.
- **4.4.1.6.** The user company should create maintenance cards by adhering to machine related plans and machine information and maintenance dates on these cards and warranty periods, changed part information which is changed under the machine warranty or out of warrant, must be present.
- **4.4.1.7.** During cleaning, maintenance and troubleshooting, care should be taken not to damage the machine safety system. At the end of all activities, when maintenance is carried out, it should be checked whether the security system is working or not.
- **4.4.1.8.** During cleaning, maintenance and troubleshooting, encountering a situation that will cause serious problems with the machine or a malfunction in any part of it, in the event of a problem that will cause wear and tear, malfunctions during operation in the future, it is absolutely necessary to provide support by informing the authorized service technical staff according to the authorized service information given below.







- 4.4.2. ELECTRICAL SYSTEM MAINTENANCE INFORMATION:
- **4.4.2.1.** Electrical control panel must be technically checked before every occupation.
- 4.4.2.2. Information on electrical and circuit diagrams of AOSM 40 Electrically Angled Automatic Sizing Machine is presented on pages 5 6, item 2.6. They were informed in detail.
- 4.4.2.3 In the unit (control panel) that ensures the operation of the electrical system of the machine, if there is a part to be replaced when necessary during the maintenance, cleaning and troubleshooting stages, the electrical connection must be cut off and the activity must be carried out by checking it by competent personnel. A visible sign (MAINTENANCE IS AVAILABLE) should be hung on the control panel by the person responsible for electrical maintenance or repair of malfunctions in order to prevent any intervention or operation by others.
- ELECTRIC DANGER
- **4.4.2.4.** In case of malfunctions related to the electrical system, especially part changes within the scope of the warranty period, it is absolutely necessary to inform the authorized service technical staff according to the authorized service information given below and to obtain support.
- **4.4.2.5.** All electrical components and units of the machine should be subjected to general maintenance, cleaning and control every six months, and the observations should be recorded with a maintenance card.
- **4.4.3. MECHANICAL MAINTENANCE INFORMATION:**
- **4.4.3.1.** All rails of the machine should be cleaned daily and proper walking operation should be provided.
- **4.4.3.2.** Before each work, all mechanical parts must be visually checked by the responsible person and if there is any nonconformity, it must be corrected.
- 4.4.3.3. The pulley bolts of the machine should be checked.
- **4.4.3.4.** The machine operator should always check the functions of all the buttons on the control panel.
- 4.4.3.5. It must be checked before every work whether sufficient water is supplied to the water valves for the purpose of cooling the cutting wires, and if there is any blockage, the waterways must be cleaned and

APPROACHING
MACHINES IN
MOVEMENT WITH
CIVIL DRESS IS
PROHIBITED.










USER GUIDE					
Document Code No	Release Date	Revision Date	Revision No		
CE-11 - 009 28.10.2016 03.11.2020 02					
This deconocide MADTANIA	D MACHINEDY AND HVDDAILLIOC	INDUCTOR TO A DE L'ED. COMPANIVI.	All alabets and account		

sufficient flow must be ensured by checking with pressure.

4.4.3.6. After the operator completes his work on the machine after each work, the workpiece wastes on the machine, dust, dirt, any-foreign materials etc. must be cleaned and the machine should be ready for reuse. In the meantime, if there is any nonconformity observed in the machine, the maintenance and repair person should be informed. If the issue is a problem that cannot be remedied by the responsible person, technical support should be provided by contacting our authorized service.





4.4.3.8. During the maintenance of the machine, water, oil, spillage of iquid substances etc. to the electrical components and control panels must be prevented.

4.4.4. MACHINE LUBRICATION INFORMATION:

4.4.4.1. The AOSM 40 Electrically Angled Automatic Sizing Machine must be lubricated once a month by the person responsible for lubrication with gress holders.

4.4.4.2. The oils to be used;

a) Rubberized grease must be applied to the car reels.

b) Grease must be applied to the bearings in the drum bearings.

4.4.4.3. After each cutting, the pulley and walking rails must be checked and cleaned.

4.4.4.4. During the lubrication maintenance activity, the relevant oils should not contaminate the electrical components.

4.4.5. POSSIBLE FAULTS, CAUSES AND SOLUTIONS:

4.4.5.1. If the machine cannot find the speed you want;

a) Electric supply power is weak.

b) The cutting wire used is excessive. The wire may not be rotating.

4.4.5.2. If the machine is running but not walking;

a) There may be a problem with the travel mechanism. (congestion, dirt, etc.)

b) The motor may be burnt or broken.

4.4.5.3. If the pulley rotates unbalanced;

a) It is possible that the original pulley may have changed.

b) The pulley attachment bolt may be loose.

c) The pulley may have been hit during operation.

4.4.5.5. When faced with possible malfunction related to the reasons mentioned above, company maintenance and repair supervisor can correct the malfunctions duly or you can get technical support from our authorized service. If you experience any malfunction or negativity other than these, you can ask for support from our authorized service.





4.4.5.6. In the event of malfunctions occurring in the machines covered by the guarantee, if the user company reaches the solution of the malfunctions by its own means without notifying our authorized service, or if any part is changed, the relevant machine is out of the guarantee and our company (manufacturer) cannot be held responsible.











U	SE	RG	W)	DF


Document Code No	Release Date	Revision Date	Revision No
CE-11 - 009	28.10.2016	03.11.2020	02

5. SAFETY AND REQUIRED WARNING INFORMATION:

To persons and organizations that will own this machine, renters, responsible users, working personnel, temporary users, user subcontractors, maintenance and repair supervisors; It is a general safety requirement to apply and comply with the mandatory conditions to be complied with as per the ISG Law, Related Necessary Legislations and all plans, instructions, lists, warning notices and working conditions defined in accordance with the Occupational Health and Safety Law in the company (in the area of use).

5.1. GENERAL SAFETY RULES:

- 5.1.1. Personnel who will use and maintain the machine has the age in accordance with the age limit determined by the laws, has acquired knowledge with the machine, is received the necessary training, knows his personal responsibilities. It is a legal requirement to have been trained in machinery and first aid in emergencies. It is absolutely essential that the responsible persons who will work with the machine have this competence.
- 5.1.2. Operators or technical personnel, responsible persons, who will operate the machine and repair electrical technical maintenance or malfunctions ust have a competent staff, must receive detailed technical training about the machine, attandance must be absolutely necessary during the first start-up and test processes; should be able to read and understand the user manual and inform third parties when necessary.
- 5.1.3. This Machine user manual should always be in a safe and easily accessible place next to the machine. This manual must be read by those who will directly or indirectly work on the machine.
- 5.1.4. During work of AOSM 40 Electrically Angled Automatic Sizing Machine, no person other than those responsible should approach, and absolutely no living things should be allowed into the safe working area specified below. Persons in charge should not climb on top of the machine while working; no limbs or foreign parts, tools or materials should be inserted into the closed areas of the machine nor into the cutting and moving mechanisms.











	USER C	SUIDE

 Document Code No
 Release Date
 Revision Date
 Revision No

 CE-11 - 009
 28.10.2016
 03.11.2020
 02

This document is KAPTANLAR MACHINERY AND HYDRAULICS INDUSTRY TRADE LTD. COMPANY's. All rights are reserved.

No part of this publication my be used or changed without the permission of the publisher. Con not be stored in a system to be used again and con not be reproduced by electronically or mechanical photocopying. Bound copies are invalid. This kind of people and organizations in the legal process is initiated initiatives.

In the safe working area specified in the upper diagram, in the area (1m), no one other than the operators whose responsibility is assigned to the safe work area can enter the working time. In cases where it is necessary to enter this area, it is absolutely necessary to stop machine. This area is entered after making sure that all moving parts and mechanisms are stopped.

- 5.1.5. During all machine maintenance, cleaning and repair activities, it must be ensured that the electrical circuit is closed and cut.
- 5.1.6. During the operation of the machine, accidents such as cutting, crushing, impact, scratching may occur in any living part, it is a legal requirement that all personnel and other persons comply with the warning rules and signs on the machine and below in order to avoid these accidents.
- 5.1.7. AOSM 40 Electrically Angled Automatic Sizing of the Machine ensuring safe working activities, technical and safe competencies, avoiding any negativity or accidents during working in the purchasing establishments. Our machine, which was produced in accordance with the following regulations and standards with the aim of minimizing possible negativities, is delivered to you after all controls are carried out, and it has been conveyed to you as information in order to create a safe working environment.
- **5.1.8.** In case of a possible problem that may occur in the electrical system of the machine or during the operation of the machine, immediately turn off the <u>machine with the Stop button</u>.
- 2006/42 EC Machinery Safety Directive
- 2006/95/AT- 2006/95/EC Low Voltage Directive (LVD)
- TSEK Product Certificate Criteria, CE Marking Regulation, İ.S.G. law, F.U.K. requirements
- TS EN ISO 12100:2010 2011 Machinery Safety General Principles for Design Risk Values and Reduction
- TS EN ISO 12100 –1 Safety in Machinery, Basic Concepts, Principles for Design, T. Terminology, Methodology
- TSEN ISO 12100 –2 Safety in Machinery, Basic Concepts, General Principles for Design, B.2 Technical Principles
- TS EN ISO 13850 Machinery Safety, Emergency Stop Equipment, Design Principles
- TS EN 953+A:2011 ∞ TS EN ISO 14120 Safety in Machinery Protectors General specifications for construction
- TS EN 6020 4-1 Safety in Machinery, Electrical Equipment of Machines Part: 1 General rules
- TS EN ISO 4414 Safety and General Rules for Machinery Fluid Power Systems, Components

5.2. WARNING AND CAUTION INFORMATION:





WORK SAFETY
INSTRUCTIONS
AND NOTICES
TO DEFINITELYS
OBEY



*In order to provide a safe working environment for the safety of machine buyers, all users and those who are indirectly in the working environment, and to prevent possible accidents and risks, the necessary safety warnings are listed below in this user manual and necessary safety, warning, prohibition signs are indicated.

5.2.1. Before using the machine, read and understand the user manual. Comply with all Occupational Health and Safety Instruction Plan and work order lists of the area of use. Be sure to comply with all the items in this user manual. Read and inform all concerned about the working environment. Keep this user manual in an accessible place next to the machine. Be sure to adhere to this User Guide. Be sure to warn those who do not follow the guidelines.











Document Code No	Release Date	Revision Date	Revision No
CE-11 - 009	28.10.2016	03.11.2020	02

This document is KAPTANLAR MACHINERY AND HYDRAULICS INDUSTRY TRADE LTD. COMPANY's. All rights are reserved. No part of this publication my be used or changed without the permission of the publisher. Con not be stored in a system to be used again and con not be reproduced by electronically or mechanical photocopying. Bound copies are invalid. This kind of people and organizations in the legal process is initiated initiatives.


- 5.2.2. In case of moving the machine to the working area or changing its location for any reason, in order not to be exposed to such risks of accident, possible crushing injury, etc., these activities should be carried out by authorized persons with business knowledge. During this work, it is strictly forbidden for anyone to approach the boundaries of the Safe Working Area (see 5.1.4.) except those in charge.
- 5.2.3. For safe operation by users during machine operation, breakdown and maintenance activities, make sure to use protective materials according to the working activity.
- 5.2.4. Do not operate the machine without making general checks without making sure that the machine parts and all equipment are mounted.
- 5.2.5. No personnel, other than the responsible person who has received training, can use the machine, do the maintenance, perform repair and fault activities. Our technical staff will provide orientation and information training to users of the each purchased machine.
- 5.2.6. Use clothing suitable for working while the machine is working; loose dresses are risky for your working safety. Do not wear.
- 5.2.7. Do not touch the moving parts while the machine is working. The machine should not be interfered with the wires during cutting. Do not put your hands and arms in the movement zone of the car. In the meantime, occupational accident hazard rate is high for crushing, cutting, etc.
- 5.2.8. Do not touch electrical components during machine operation, and do not open the cover of the electrical panel. Electricity and high voltage can cause serious injury or death.

Therefore, Cut off the power at the switch before maintenance and troubleshooting, etc. Make sure that the electrical input of the machine is cut off. 5.2.9. In the event of a possible danger during machine operation, stop the machine

immediately. Do not operate the machine until the danger has been removed.

5.2.10. Do not engage in such activities of leaning, maintenance, adjustment, etc. while the machine is running. It is absolutely dangerous for your safety.

5.2.11. Never operate the machine without being responsible without taking all safety precautions. Do not forget that inattention and ignorance bring accidents!





















THREAT AREA, IT IS

DANGEROUS.

















Document Code No	Release Date	Revision Date	Revision No
CE-11 - 009	28.10.2016	03.11.2020	02

This document is KAPTANLAR MACHINERY AND HYDRAULICS INDUSTRY TRADE LTD. COMPANY's. All rights are reserved.

No part of this publication my be used or changed without the permission of the publisher. Con not be stored in a system to be used again and con not be reproduced by electronically or mechanical photocopying. Bound copies are invalid. This kind of people and organizations in the legal process is initiated initiatives.

WORK SAFETY
INSTRUCTIONS
AND NOTICES
TO DEFINITELYS
OBEY









5.4. AOSM 40 Electrically Angled Automatic Sizing Machine, The Precautionary, Warning and Prohibition Signs that must be on the machine are listed below.













The products in this User's Guide are produced and factory production controlled in our certified institution in compliance with the regulations and standards specified, are by subject to ISO 9001:2015 Quality Management System, TSE HYB, TSEK, meeting the requirements of the 2006/42 EC Machinery Safety Regulation and the 2006/95 EC Low Voltage Regulation referred to CE on the Product Safety.